

REX

www.rexind.co.jp

NP50AV


PIPE THREADING MACHINE

Economical and Highly Efficient Superb Quality and Reliability !



NP50AV

ISO9001 : JQA-2387 / ISO14001 : JQA-EM2926



Threading

- **USER FRIENDLY** and **EASY MAINTENANCE.**
- Small but powerful 700W (output) series motor.
- Easy to use, high productivity, excellent portability - only 48kg.



NV-type Die head

- Pipe size can be adjusted simply by turning the lever nut.
- Thread length can be adjusted by just changing the lever contact.
- Uses auto-stop carbon brushes to prevent damage to the motor.
- The NV-type die head can be opened manually or automatically.

■ Specifications

Model	NP50AV
Threading Capacity	1/2B - 2B (15A - 50A)
Voltage (50/60Hz)AC (V)	115 or 220 or 230
Rotation Speed (min ⁻¹)	39 (unloaded)
Weight (kg)	48
Dimensions L×W×H (mm)	700×440×408

■ Optional Items

Portable Groover M



RG-R1 with NP50A

- Grooves 1" to 6" Schedule 10 steel and 1" to 3" Schedule 40 steel pipes.
- Easy to attach to your current REX N50A, R50A, P50A, NR50A, NP50A, N80A, S80A, N100A, RIDGID #300 or 300 Compact.
- As with the Light Groove 150DX, the groove depth is easily adjusted. Further, grooving is possible with minimum force using REX' original power mechanism.
- Compact and lightweight with excellent durability.



RG-R1

REX INDUSTRIES CO.,LTD.

Overseas Sales Dept. & Factory

1-9-3, Hishiya-Higashi, Higashi-Osaka 578-0948 Japan
Tel. +81-(0)72-961-9820 Fax +81-(0)72-961-9878

- Be sure to read the Operation Manual before use.
- Changes in specifications, colour, etc. may be made without prior notification.
- For environmental considerations, this catalogue has been printed using soy ink and recycled paper.



0907AB02-E1

